

Application No. 09/883,592  
Attorney Docket No. 0383-1-1

The listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (Canceled) A combination of a towing vehicle mounting and a vehicle connection member: comprising a generally rectangular channel for telescopically engaging a complementary rectangular member, whereby said members may be removably secured together by a locking pin, a trailer featuring a load bearing frame, and a hitching mechanism for attaching said trailer to said generally rectangular channel,  
  
said trailer comprising a generally horizontally disposed frame having a front member, a rear member and a pair of side members, a pair of at least one horizontally pivotal wheel assemblies mounted to said frame, where said at least one wheel assemblies may be pivoted up to about 360 degrees, and a hitching mechanism secured to said front member, said hitching mechanism comprising a first generally rectangular channel member fixed to said front member, and a generally rectangular pivotal member mounted at a first end thereof for pivotal movement in a vertical plane relative to said fixed channel, with a second free end for telescopically engaging said generally rectangular member on said towing vehicle.
2. (Canceled) The combination of Claim 1, wherein said vertically pivotal member includes a continuous body portion having a pair of opposing walls extending therefrom, where said side walls include apertures for receiving a pivot pin for engaging complementary apertures in said fixed channel member.
3. (Canceled) The combination of Claim 1, wherein each said wheel assembly comprises a U-shaped housing having a base with a pair of parallel walls extending therefrom, said base being pivotally mounted to said frame and said walls rotatably mount a wheel.

Application No. 09/883,592  
Attorney Docket No. 0383-1-1

4. (Canceled) The combination of Claim 1, wherein said generally disposed horizontal frame includes plural intermediate frame members to provide rigidity and flooring support to said trailer.
5. (Canceled) The combination of Claim 1, wherein said first generally rectangular member includes a vertically oriented arcuate slot, and said generally rectangular pivotal member is mounted for rotative and vertical movement within said arcuate slot.
6. (Canceled) The combination of Claim 1, wherein at least said first generally rectangular member includes a pair of vertically mounted plate members, where said plate members further include arcuate slots to allow limited vertical movement of said hitching mechanism.
7. (Canceled) The combination of Claim 6, wherein said generally rectangular pivotal member also includes a pair of vertically mounted plate members, also including arcuate slots to facilitate limited vertical movement of said hitching mechanism.
8. (Canceled) The combination of Claim 7, wherein there are a pair of spaced-apart hitching mechanisms extending between said towing vehicle and said trailer.

Application No. 09/883,592  
Attorney Docket No. 0383-1-1

9. (Canceled) A limited nonarticulating trailer and hitch mechanisms for mounting to a towing vehicle having a generally rectangular or tubular (female) channel for telescopically engaging a complementary rectangular or tubular (male) member on said towing vehicle,

said trailer comprising a horizontally disposed load bearing frame consisting of at least a front channel member, a rear channel member and a pair of spaced-apart side channel members extending between said front and rear members, a central channel member extending forward from said rear member to beyond said front member and terminating in a free end and forming part of said hitch mechanism, and at least one swivel wheel assembly mounted along said rear channel member, where said at least one wheel assembly are is pivotal about at 360 degrees, and said hitch mechanism consisting of said free (female) end having a pair of aligned apertures for receiving a pivot pin, and a generally rectangular pivotal member mounted for pivotal movement in a vertical plane about said pivot pin, said generally rectangular pivotal member featuring a rectangular body portion and a pair of opposing wall portions extending from said body portion, where said opposing wall portions are spaced-apart to slidably and rotatably receive and engage said free end, where the opposite end of said body portion is sized to be slidably engaged with said generally rectangular or tubular (male) channel of said towing vehicle.

10. (Canceled) The limited nonarticulating trailer and hitch mechanism of Claim 5 9, wherein each said wheel assembly comprises a generally U-shaped housing having a base with a pair of parallel walls extending therefrom, said base being pivotally mounted to said frame and said walls rotatably mount a said wheel assembly.

11. (Canceled) The limited articulating trailer and hitch mechanism of Claim 9, wherein said aligned slots are arcuate shaped to allow limited vertical movement of said trailer traversing uneven terrain.

Application No. 09/883,592  
Attorney Docket No. 0383-1-1

12. (Canceled) The limited articulating trailer and hitch mechanism of Claim 9, wherein said free end mounts a pair of vertically oriented plates, and said aligned apertures consist of aligned arcuate slots.

13. (New) A vehicle trailer and trailer hitch assembly for being received by a vehicle hitch assembly, comprising:

- a) a trailer comprising,
  - i) a generally rectangular frame of rigid members,
  - ii) an elongated hitch tongue member extending from said frame, said hitch tongue member having at least one vertical arcuate slot defined therein,
  - iii) a pin pivotably receivable within said at least one slot,
- b) a trailer hitch mountable to said vehicle hitch assembly, comprising,
  - i) an elongated hitch connection member having a pair of opposing generally parallel fingers extending therefrom, each finger having an aperture defined therein for receiving said pin such that said trailer hitch can vertically pivot, vertically slide and have limited rotational movement within said slot with respect to said elongated hitch member; and,
- c) a plurality of wheel assemblies associated with said frame, each wheel assembly being capable of 360 degree swiveling about a vertical axis.

14. (New) The vehicle trailer and trailer hitch assembly of Claim 13, wherein said at least one arcuate slot comprises a pair of arcuate slots defined on opposite sides of said hitch tongue member.